

# Standard Len-Tex® Vinyl Offering

 Arani Silk	 Lennon Grass	 Loominous
 Lotus 511 (S) 547 (H)	 Pumila Grass 517 (S) 553 (H)	 Canvas 523 (S) 559 (H)
 Adrift 512 (S) 548 (H)	 Oats 518 (S) 554 (H)	 Bobbin Weave 524 (S) 560 (H)
 Reed 513 (S) 549 (H)	 Prairie 519 (S) 555 (H)	 Threads 525 (S) 561 (H)
 Sandalwood 514 (S) 550 (H)	 Reed 520 (S) 556 (H)	 Common Thread 526 (S) 562 (H)
 Veranda 515 (S) 551 (H)	 Red Oat 521 (S) 557 (H)	 Quill 527 (S) 563 (H)
 Slate 516 (S) 552 (H)	 Feather Grass 522 (S) 558 (H)	 Lustre 528 (S) 564 (H)

Note: Each digital swatch is a digital color presentation of a standard color and is subject to minor shade variations.

# Standard Len-Tex® Vinyl Offering

 Coronado	 Soraya	 Emboss LT Suede
 White 529 (S) 565 (H)	 Arctic 535 (S) 571 (H)	 B. White 541 (S) 577 (H)
 Silver Dust 530 (S) 566 (H)	 Serenity 536 (S) 572 (H)	 Eggshell 542 (S) 578 (H)
 Cirrus 531 (S) 567 (H)	 Grey Pearl 537 (S) 573 (H)	 Frost Taupe 543 (S) 579 (H)
 Camel Down 532 (S) 568 (H)	 Willet 538 (S) 574 (H)	 Aspen 544 (S) 580 (H)
 Cimmerin 533 (S) 569 (H)	 Windrift 539 (S) 575 (H)	 Denver 545 (S) 581 (H)
 Carbon 534 (S) 570 (H)	 Hemp 540 (S) 576 (H)	 Black 546 (S) 582 (H)

Displayed samples feature a standard weight 20-oz. (S). Also available in a heavy-duty 30-oz. construction (H).



## Len-Tex® Vinyl Wallcovering Finish Specifications

	<b>U.S. Units</b>	<b>Metric Units</b>		<b>U.S. Units</b>	<b>Metric Units</b>
Total Weight:	20.0 oz./LY	612 G/LM	Total Weight:	30.0 oz./LY	925 G/LM
	13.2 oz./SY	442 G/SM		20.0 oz./SY	680 G/SM
Fabric Weight:	2.5 oz./LY	85 G/LM	Fabric Weight:	5.5 oz./LY	170 G/LM
Vinyl Weight:	17.5 oz./LY	520 G/LM	Vinyl Weight:	24.5 oz./LY	756 G/LM
Material Width:	53/54"	134/137 cm	Material Width:	53/54"	134/137 cm
Fabric Type:	Poly Cotton Osnaburg		Fabric Type:	Poly Cotton Drill	

### Federal Specifications:

Len-Tex Clean Vinyl Wallcovering meets or exceeds all requirements of W-101 (20 oz), W-101, Type III (30 oz.) Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings. This product has been accepted for use by the City of New York Dept. of Buildings under MEA-381-93M.

### Fire Hazard Classification Results:

**ASTM E-84** Tunnel Test: Class A, Flame Spread: 15; Smoke Developed: 10 (20 oz.)  
**ASTM E-84** Tunnel Test: Class A, Flame Spread: 20; Smoke Developed: 65 (30 oz.)  
**PASS** rating as tested under NFPA 286 (Corner burn test)  
**CAN/ ULC S102-10** Fire Test: Class A, Flame Spread: 15; Smoke Developed: 75  
**EN 13501-1** Fire Classification: B-s2, d0

### Performance Features:

Len-Tex Wallcoverings use **Clean Vinyl Technology™**  
 Phthalate-free  
 Alumina trihydrate fire retardant (antimony-free)  
**Ultra-Fresh®** antimicrobial (non-arsenate)  
 No heavy metals or formaldehyde  
 Printed exclusively with water-based, low VOC **AQUA-CLEAR™** inks  
 Roller applied **AQUA-CLEAR 3.0™** top finish for improved stain resistance  
 Microventing for permeability is available on a custom order basis  
 Advanced Warning Effect (ionization-type smoke detector)  
 Five year warranty against materials defects – Consult your distributor for details

### Environmental Attributes:

Ultra-low emitting – Pass rating under CA 01350  
 Listed by ZeroDocs and Sustainable Minds® for California CHPS (Collaborative for High Performance Schools) SCS Indoor Advantage™ Gold certified  
 CA Prop 65 compliant  
 Published Health Product Declaration (HPD) – LEED eligible  
 Published Len-Tex Environmental Product Declaration (EPD) – LEED eligible  
 GreenCircle Certified™

### Find Len-Tex products listed on:

Ecomedes (ecomedes.com), SCS Global Services website (scsglobalservices.com), GreenCircle Certified website (greencirclecertified.com), Mortarr (mortarr.com)

### Permeability, Moisture and Mold:

Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration. To reduce the risk of fungal growth, Len-Tex recommends that all wallcovering(s) be microvented when installed in Humid and Fringe Zone 1 climates.(ref: ASHRAE Handbook of Fundamentals, Chapter 21, Figure 16). Please see full details on microventing at our website, [lentexwallcoverings.com](http://lentexwallcoverings.com).



800-869-9685 | [info@modernfold.com](mailto:info@modernfold.com) | [www.modernfold.com](http://www.modernfold.com)  
 215 West New Rd. | Greenfield, IN 46140

# VINYL SELECTOR

