

# Premium Woodgrain Len-Tex® Vinyl Offering



Early American Maple  
597 (S) 615 (H)



Honey Maple  
593 (S) 611 (H)



Sunset Maple  
596 (S) 614 (H)



Natural Walnut  
594 (S) 612 (H)



Dark Walnut  
598 (S) 616 (H)



Barnboard Walnut  
586 (S) 604 (H)

# Premium Woodgrain Len-Tex® Vinyl Offering



Sandalwood Ash  
583 (S) 601 (H)



Pickled White Oak  
591 (S) 609 (H)



Tobacco White Oak  
599 (S) 617 (H)



Jacobean White Oak  
589 (S) 607 (H)



Shoreline Ash  
588 (S) 606 (H)



Rustic Rift White Oak  
584 (S) 602 (H)



Rift & Quartered White Oak  
585 (S) 603 (H)



Tigerwood  
600 (S) 618 (H)



Espresso Ash  
590 (S) 608 (H)



Golden Rift White Oak  
595 (S) 613 (H)



Aged Rift White Oak  
587 (S) 605 (H)



Ebony  
592 (S) 610 (H)

Note: Each swatch is a color presentation of a standard color and is subject to minor shade variations.

Displayed samples feature a standard weight 20-oz. (S). Also available in a heavy-duty 30-oz. construction (H).

## Len-Tex® Vinyl Wallcovering Finish Specifications

	U.S. Units	Metric Units		U.S. Units	Metric Units
Total Weight:	20.0 oz./LY	612 G/LM	Total Weight:	30.0 oz./LY	925 G/LM
	13.2 oz./SY	442 G/SM		20.0 oz./SY	680 G/SM
Fabric Weight:	2.5 oz./LY	85 G/LM	Fabric Weight:	5.5 oz./LY	170 G/LM
Vinyl Weight:	17.5 oz./LY	520 G/LM	Vinyl Weight:	24.5 oz./LY	756 G/LM
Material Width:	53/54"	134/137 cm	Material Width:	53/54"	134/137 cm
Fabric Type:	Poly Cotton Osnaburg		Fabric Type:	Poly Cotton Drill	

### Federal Specifications:

Len-Tex Clean Vinyl Wallcovering meets or exceeds all requirements of W-101 (20 oz), W-101, Type III (30 oz.) Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings. This product has been accepted for use by the City of New York Dept. of Buildings under MEA-381-93M.

### Fire Hazard Classification Results:

**ASTM E-84** Tunnel Test: Class A, Flame Spread: 15; Smoke Developed: 10 (20 oz.)

**ASTM E-84** Tunnel Test: Class A, Flame Spread: 20; Smoke Developed: 65 (30 oz.)

**PASS** rating as tested under NFPA 286 (Corner burn test)

**CAN/ ULC S102-10** Fire Test: Class A, Flame Spread: 15; Smoke Developed: 75

**EN 13501-1** Fire Classification: B-s2, d0

### Performance Features:

Len-Tex Wallcoverings use **Clean Vinyl Technology™**

Phthalate-free

Alumina trihydrate fire retardant (antimony-free)

**Ultra-Fresh®** antimicrobial (non-arsenate)

No heavy metals or formaldehyde

Printed exclusively with water-based, low VOC **AQUA-CLEAR™** inks

Roller applied **AQUA-CLEAR 3.0™** top finish for improved stain resistance

Microventing for permeability is available on a custom order basis

Advanced Warning Effect (ionization-type smoke detector)

Five year warranty against materials defects – Consult your distributor for details

### Environmental Attributes:

Ultra-low emitting – Pass rating under CA 01350

Listed by ZeroDocs and Sustainable Minds® for California CHPS (Collaborative for High Performance Schools) SCS Indoor

Advantage™ Gold certified

CA Prop 65 compliant

Published Health Product Declaration (HPD) – LEED eligible

Published Len-Tex Environmental Product Declaration (EPD) – LEED eligible

GreenCircle Certified™

### Find Len-Tex products listed on:

Ecomedes (ecomedes.com), SCS Global Services website (scsglobalservices.com), GreenCircle Certified website (greencirclecertified.com), Mortarr (mortarr.com)

### Permeability, Moisture and Mold:

Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration. To reduce the risk of fungal growth, Len-Tex recommends that all wallcovering(s) be microvented when installed in Humid and Fringe Zone 1 climates.(ref: ASHRAE Handbook of Fundamentals, Chapter 21, Figure 16). Please see full details on microventing at our website, [lentexwallcoverings.com](http://lentexwallcoverings.com).



800-869-9685 | [info@modernfold.com](mailto:info@modernfold.com) | [www.modernfold.com](http://www.modernfold.com)  
215 West New Rd. | Greenfield, IN 46140



# PREMIUM VINYL SELECTOR