

OPERABLE PARTITIONS

# Single Panel Systems Spec Sheet

ACOUSTI-SEAL® MODEL	ENCORE™	931	911
Acoustics - STC	56, 54, 52	52, 50, 47, 41, 28*	52, 50, 45
Panel Thickness - Nominal	4.25" (108 mm)	3" (76 mm)	3" (76 mm)
Operation	Single Panel Manual	Single Panel Manual	Single Panel Manual
Frame	Roll Formed & Welded 16 Gage Steel	Roll Formed & Welded 16 Gage Steel	Roll Formed & Welded 16 Gage Steel
Finish Options	Vinyl, Heavy Duty Vinyl, Carpet, Fabric, Customers Own Material, Full Height Marker/Tack Board, Uncovered	Vinyl, Heavy Duty Vinyl, Carpet, Fabric, Customers Own Material, Full Height Marker/Tack Board, Plastic Laminate, Wood Veneer, Uncovered	Vinyl, Heavy Duty Vinyl, Carpet, Fabric, Customers Own Material, Full Height Marker Board, Uncovered
Skin/Face Options	Steel	Steel, Gypsum, MR Board, MDF Board	Steel
Maximum Opening Width	Unlimited	Unlimited	Unlimited
Maximum Height	60' (18,288 mm)	30' (9144 mm)	30' (9144 mm)
Hanging Weight (lbs/sq.ft.) - STC dependent	8 to 12	6 to 11	8 to 11
Track Options	#17, #14 RT100, RT200	#17, #14 RT100, RT200	#17, #14
Pass Door Selections	Single Matching Construction, Double Matching Construction	Single Hollow Metal, Double Hollow Metal, Single Matching Construction, Double Matching Construction	Single Matching Construction, Double Matching Construction
Top/Bottom Seals	Top: Automatic  Bottom: SureSet™ 2" Automatic SureSet™ 2" Manual SureSet™ 4" Automatic SureSet™ 4" Manual	Top: Fixed Sweep  Bottom: 2" Automatic 2" Manual	Top: Fixed Sweep  Bottom: 2" Automatic 2" Manual 4" Manual
*Consult your local Modernfold distributor for custom options including: Finishes, cutouts and alternative platforms for pocket space constraints.			