

MOVABLE GLASS WALLS

Horizontal Rail Systems Spec Sheet

MODEL	COMPACTLINE	100SR-G	DRS
Rail Height & Design	4.88" (124 mm) Contoured Bottom & Top	3.94" (100 mm) Square Bottom & Top	3.62" (92 mm) Square Bottom & Top 3.62" (92 mm) Tapered Bottom & Top 6" (152 mm) Square Bottom & 3.62" (92 mm) Square Top 10" (254 mm) Square Bottom & 3.62" (92 mm) Square Top
Operation	Singel Panel Manual	Singla Panel Manual	Single Panel Manual
Rail Finish Options	Clear Anodized, Satin Stainless Anodized, Powder Coat Std RAL	Clear Anodized, Dark Bronze Anodized, Black Anodized, Satin Brass, Satin Stainless, Polished Brass, Polished Stainless, Powder Coat Std RAL	Clear Anodized, Dark Bronze Anodized, Black Anodized, Champagne, Satin Bronze, Satin Brass, Satin Stainless, Polished Bronze, Polished Brass, Polished Stainless, Powder Coat Std RAL
Glass Thickness	3/8" (10 mm) or 1/2" (13 mm)	3/8" (10 mm) or 1/2" (13 mm)	3/8" (10 mm) or 1/2" (13 mm)
Standard Glass	Clear, Tempered	Clear, Tempered	Clear, Tempered
Glass Options	Low Iron, Frosted, Etched, Silk Screen, Applique	Low Iron, Frosted, Etched, Silk Screen, Applique	Low Iron, Frosted, Etched, Silk Screen, Applique
Maximum Panel Width	4' (1219 mm)	4' (1219 mm)	4' (1219 mm)
Maximum Height	10' (3048 mm)	10' (3048 mm)	10' (3048 mm)
Maximum Panel Weight	300 lbs. (136 kg)	330 lbs. (150 kg)	330 lbs. (150 kg)
Track Options	G150	#17G, G150	#17G, G150