## **OPERABLE PARTITIONS**

## Acousti-Seal® Continuously Hinged Automated Wall Systems Spec Sheet

ACOUSTI-SEAL® MODEL	<b>ENCORE® AUTOMATED</b>	ENCORE® AUTOMATED #20	933E
Acoustics - STC	56, 54, 52	56, 54, 52	52, 50, 47, 45, 41, 28
Panel Thickness - Nominal	4.25" (108 mm)	4.25" (108 mm)	3" (76 mm)
Operation	Continuously Hinged Electric	Continuously Hinged Electric	Continuously Hinged Electric
Frame	Roll Formed & Welded 16 Gage Steel	Roll Formed & Welded 16 Gage Steel	Roll Formed & Welded 16 Gage Steel
Finish Options	Vinyl, Heavy Duty Vinyl, Carpet, Fabric, Customers Own Material, Full Height Marker/ Tack Board, Uncovered	Vinyl, Heavy Duty Vinyl, Carpet, Fabric, Customers Own Material, Full Height Marker/ Tack Board, Uncovered	Vinyl, Heavy Duty Vinyl, Carpet, Fabric, Customers Own Material, Full Height Marker, Tack Board, Plastic Laminate, Wood Veneer, Uncovered
Skin/Face Options	Steel	Steel	Steel, MDF Board
Maximum Opening Width	133'-9" (single); 267'-0" (pair) (40767 mm; 81382 mm)	235'-9" (single); 471'-0" (pair) (71857 mm; 143561 mm)	164'-11" (single); 329'-7"(pair) (50267 mm; 100457 mm)
Maximum Height	24' (7315 mm)	40' (12192 mm)	28' (8534 mm)
Hanging Weight (lbs/sq.ft.) - STC dependent	8 to 12	8 to 12	6 to 11
Track Options	#14, #30	#20	#14, #30
Pass Door Selection	Single Matching Construction	Single Matching Construction	Single Matching Construction
Top/Bottom Seals	Top: Automatic Bottom: Sureset 2" Automatic: Sureset 2" & 4" Touch Seal	Top: Automatic Bottom: Sureset 2" Automatic: Sureset 2" & 4" Touch Seal	Top: Fixed Sweep Bottom: 2" Automatic Floating Seal