

MOVABLE GLASS WALL SYSTEMS

Horizontal Rail Systems Spec Sheet

MODEL	COMPACTLINE	PUREVIEW	DRS
Acoustics - STC	15 STC 26 STC Fully Framed	15 STC	15 STC 18 STC Fully Framed
Rail Height & Design	4.88" (124 mm) Contoured Bottom & Top	4.12" (105 mm) Square Bottom & Top	3.62" (92 mm) Square Bottom & Top 3.62" (92 mm) Tapered Bottom & Top 6" (152 mm) Square Bottom & 3.62" (92 mm) Square Top 10" (254 mm) Square Bottom & 3.62" (92 mm) Square Top
Operation	Single Panel Manual	Single Panel Manual	Single Panel Manual
Rail Finish Options	Clear Anodized, Satin Stainless Anodized, Powder Coat Std RAL	Clear Anodized, Dark Bronze Anodized, Black Anodized, Satin Stainless Anodized, Powder Coat Std RAL	Clear Anodized, Dark Bronze Anodized, Black Anodized, Satin Brass, Satin Stainless, Polished Brass, Polished Stainless, Powder Coat Std RAL
Glass Thickness	1/2" (13 mm)	1/2" (13 mm)	1/2" (13 mm)
Standard Glass	Clear, Tempered	Clear, Tempered	Clear, Tempered
Glass Options	Low Iron, Frosted, Etched, Applique, Polar White Markerboard Glass	Low Iron, Frosted, Etched, Applique, Polar White Markerboard Glass	Low Iron, Frosted, Etched, Applique, Polar White Markerboard Glass
Maximum Panel Width	4' (1219 mm)	4' (1219 mm)	4' (1219 mm)
Maximum Height	10' (3048 mm)	10' (3048 mm)	10' (3048 mm)
Maximum Panel Weight	300 lbs. (136 kg)	330 lbs. (150 kg)	330 lbs. (150 kg)
Track Options	G330	G330	G330, #17G
Track Options	G330, #17G	G330, #17G	N/A