

OPERABLE PARTITIONS

Acousti-Seal® Single Panel Systems Spec Sheet

ACOUSTI-SEAL® MODEL	ENCORE®	931	911 - FIRE RATED
Acoustics - STC	56, 54, 52	52, 50, 47, 41, 28*	52, 50, 45
Panel Thickness - Nominal	4.25" (108 mm)	3" (76 mm)	3" (76 mm)
Operation	Single Panel Manual	Single Panel Manual	Single Panel Manual
Frame	Roll Formed & Welded 16 Gage Steel	Roll Formed & Welded 16 Gage Steel	Roll Formed & Welded 16 Gage Steel
Finish Options	Vinyl, Heavy Duty Vinyl, Carpet, Fabric, Customers Own Material, Full Height Marker/Tack Board, Uncovered	Vinyl, Heavy Duty Vinyl, Carpet, Fabric, Customers Own Material, Full Height Marker/Tack Board, Plastic Laminate, Wood Veneer*, Uncovered	Vinyl, Heavy Duty Vinyl, Carpet, Fabric, Customers Own Material, Full Height Marker Board, Uncovered
Skin/Face Options	Steel	Steel, Gypsum, MR Board, MDF Board*	Steel
Maximum Opening Width	Unlimited	Unlimited	Unlimited
Maximum Height	60' (18,288 mm)	30' (9144 mm)	30' (9144 mm)
Hanging Weight (lbs/sq.ft.) - STC dependent	8 to 12	6 to 11	8 to 11
Track Options	#17, #14, RT100, RT200	#17, #14, RT100, RT200	#17, #14
Pass Door Selection	Single Matching Construction, Double Matching Construction	Single Hollow Metal, Double Hollow Metal, Single Matching Construction, Double Matching Construction	Single Matching Construction, Double Matching Construction
Top/Bottom Seals	Top: Automatic Bottom: SureSet™ 2" Automatic, SureSet™ 2" Manual, SureSet™ 4" Automatic, SureSet™ 4" Manual	Top: Fixed Sweep Bottom: 2" Automatic, 2" Manual	Top: Fixed Sweep Bottom: 2" Automatic, 2" Manual, 4" Manual
<i>*Consult your local Modernfold distributor for custom options including: Finishes, cutouts and alternative platforms for pocket space constraints.</i>			